

SUNSHINE POOL COMPANY INC.
77 Mattakeesett St., Route 14
Pembroke, MA 02359

781-293-7075
Fax: 781-294-2258
www.sunshinepoolcompany.com



Mission Statement:
To provide "Only Quality Work"
by taking care of each pool as
if it were our own and treating
each customer like family.

Family owned and operated since 1971

Sunshine Pool Company

Only Quality Work

TO BACKWASH MULTIPOINT STYLE D.E. FILTER

1. Turn pump/motor off.
2. Push down to turn your multiport dial to the *Backwash* position.
3. Turn on pump/motor.
4. Allow pump/motor to run until your sight glass has run clean and clear. (compare it to the beginning of the backwash cycle) Approximately 1-2 minutes.
5. Turn off pump/motor.
6. Push down to turn your multiport dial to the *Rinse* position.
7. Turn on pump/motor and run until the sight glass is clear. Approximately 30 seconds.
8. Repeat steps #1 thru #7 at least three (3) times. You may do these steps more if your filter is excessively dirty and you have enough water in the pool to do so.
9. Turn off pump/motor
9. Push down to turn your multiport dial to the *Filter* position.
10. Turn on pump/motor.
11. Using the correct amount of D.E. (check filter for direction). Go to your skimmer and put the D.E. in the skimmer and wash it down the drain.

Your D.E. should be changed every four (4) weeks whether it needs it or not. This is to ensure a clean, and easily maintained swimming pool.

If there is algae present in your pool, the pressure gauge will rise rapidly and may have to be changed more often, along with super chlorination and the use of algacide.