

SUNSHINE POOL COMPANY INC.
77 Mattakesett St., Route 14
Pembroke, MA 02359

781-293-7075
Fax: 781-294-2258
www.sunshinepoolcompany.com



Mission Statement:
To provide "Only Quality Work"
by taking care of each pool as
if it were our own and treating
each customer like family.

Family owned and operated since 1971

Sunshine Pool Company

Only Quality Work

TO CHANGE D.E. HAYWARD PERFLEX FILTER

1. Shut off pump/motor. *Bump* handle, down slow and up fast ten (10) times.
2. Open air relief valve at top of filter.
3. At bottom of filter, open backwash valve all the way until water stops running out. Listen for the hiss of air being sucked into the filter. When the hissing sound has stopped the water has stopped as well.
4. Leaving the air valve and backwash valve open. Turn on the pump/motor. When water begins to come out of the air vent at the top of the filter, shut off the pump/motor and *Bump* the filter five (5) times. Allow the the filter to drain completely.
5. Repeat step #4 at least three (3) times. Let the filter completely drain after each time you perform step #4.
6. Close the air vent valve. Turn the pump/motor on. Look at the backwash line - make sure water is running out clean. If it is not perform step #4 again until water is clean.
7. With the pump/motor running, close and open your backwash valve at least three (3) times to make sure your valve is clean and free of debris. When finished leave in the closed position.
8. With the pump/motor running, use six (6) One pound D.E. scoops or a pre-measured six-pound bag of D.E. Go to your skimmer and put the correct dose of D.E. in the skimmer and wash it down the drain.

Your D.E. should be changed every four (4) weeks whether it needs it or not. This is to ensure a clean, and easily maintained swimming pool.

If there is algae in the pool, the pressure gauge will rise rapidly and may have to be changed more often, along with super chlorination and the use of algaecide.