

SUNSHINE POOL COMPANY INC.
77 Mattakesett St., Route 14
Pembroke, MA 02359

781-293-7075
Fax: 781-294-2258
www.sunshinepoolcompany.com



Mission Statement:
To provide "Only Quality Work"
by taking care of each pool as
if it were our own and treating
each customer like family.

Family owned and operated since 1971

Sunshine Pool Company

Only Quality Work

OPERATING YOUR CHLORINATOR

FOR INGROUND POOLS

1. Always be Cautious, when handling chlorine products.
2. Begin by turning off the electricity to your pump/motor.
3. While removing the top cover of the chlorinator, **DO NOT STAND** above the unit, and be careful not to inhale chlorine gas. Open the top lid of the chlorinator by turning it counter clockwise. (Hayward chlorinators depress the locking tab).
4. Fill with SLOW DISSOLVING jumbo tabs (3" pucks) or sticks. If possible use plastic gloves.
5. Replace the lid to the chlorinator. Double check to see if it is securely fastened.
6. Prime the pump and restore the power if needed.
7. Remember, you should always maintain a free and available chlorine level of between 1 and 3 PPM
 - Note: Chlorine product information varies. Always read the product's instructions.
 - During the winter remove all the water and tablets from the chlorinator.

ONLY USE TABLETS MADE SPECIFICALLY FOR SLOW DISSOLVING CHLORINATORS

FOR ABOVEGROUND POOLS WITH HAYWARD CHLORINATORS.

1. Always be Cautious, when handling chlorine products.
2. Begin by turning off the electricity to your pump/motor.
3. Removing the eyeball return fitting; you may need to use a plastic key to remove all of it. (These are available from our Parts Department.) Now, install the threaded plug (inside the pool). Make sure that it has a rubber o-ring that it is not split or cracked. Snap the Aquador over the lip on the skimmer face plate.
 - For easy operation, place a shut off valve in front of the motor and on the back side of the return fitting. By placing them both on the "OFF" position, you have shut off the water flow. (An available option at our store.)
4. Turn the Chlorinator to the off position.
5. While removing the top cover of the chlorinator, **DO NOT STAND** above the unit, and be careful not to inhale chlorine gas. Open the top lid of the chlorinator by depressing the locking tab and turning it counter clockwise.
6. Fill with SLOW DISSOLVING jumbo tabs (3" pucks) or sticks. If possible use plastic disposable gloves.
7. Replace the lid to the chlorinator.
8. Remove the threaded plug, Aquador or open your shut off valves.
8. Prime the pump and restore the power, if needed.
9. Remember you should always maintain a free and available chlorine level of between 1 and 3 PPM
 - During the winter remove all the water and tablets from the chlorinator.
 - Note: Chlorine product information varies, always read the products instructions.
 - NOTE: WHILE VACUUMING POOLS SHUT OFF CHLORINATORS.

ONLY USE TABLETS MADE SPECIFICALLY FOR SLOW DISSOLVING CHLORINATORS