

SUNSHINE POOL COMPANY INC.
77 Mattakeesett St., Route 14
Pembroke, MA 02359

781-293-7075
Fax: 781-294-2258
www.sunshinepoolcompany.com



Mission Statement:
To provide "Only Quality Work"
by taking care of each pool as
if it were our own and treating
each customer like family.

Family owned and operated since 1971

Sunshine Pool Company

Only Quality Work

TO BACKWASH SAND FILTER

1. Turn pump/motor off.
2. Push down to turn your multiport dial to the ***Backwash*** position.
3. Turn on pump/motor.
4. Allow pump/motor to run until your site glass has run clean and clear. (compare it to the beginning of the backwash cycle) Approximately 1-2 minutes.
5. Turn off pump/motor.
6. Push down to turn your multiport dial to the ***Rinse*** position.
7. Turn on pump/motor and run until the sight glass is clear. Approximately 30 seconds.
9. Turn off pump/motor
9. Push down to turn your multiport dial to the ***Filter*** position.
10. Turn on pump/motor.

Backwash your filter when the pressure gauge rises 10-15 lbs. above the normal operating pressure or when the pool circulation has been drastically reduced.

Backwashing your sand filter when the pressure is operating at a normal pressure will cause your filter to work improperly. Only backwash as needed.